NSN 5930-00-023-7155

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-023-7155

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.281 inches **Overall Height:** 1.312 inches **Overall Width:** 1.312 inches First Flat Length: 0.500 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.156 inches single actuator **Individual Section Quantity: Nonturn Device Type:** Flatted bushing at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 5 each section rear **Mounting Method:** Threaded bushing single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:**

Tab, solder lug

NSN 5930-00-023-7155

Rotary Switch - Page 2 of 2



\mathbf{c}	nnf	act	SW	itch	ina	ı Ac	tior	٠.
U	וווכ	acı	ЭW	ILCI	IIIIU	IAC	เเบเ	ı.

Breaks before makes each section rear

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0