

View Online at <https://aerobasegroup.com/nsn/5930-00-024-0559>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Waterproof

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

0.562 inches

Body Width:

0.354 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

Between 0.943 inches and 1.123 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 50.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Test Data Document:

81349-mils8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0