NSN 5930-00-024-0870

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-024-0870

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.020 inches
Overall Height:
2.857 inches
Overall Width:
1.000 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.330 inches
Actuator Height:
1.237 inches
Actuator Free Position Height:
1.827 inches
Housing Height:
1.780 inches
Housing Length:
2.250 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.000 inches
Maximum Voltage Rating In Volts:
125.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
Retween 26.0 gunces and 59.0 gunces

Actuator Movement:

Between 0.160 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

NSN 5930-00-024-0870

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage	Contact Load	Current Rating	At Maximum	Rated	Voltage
--	--------------	-----------------------	------------	-------	---------

3.000 amperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0