# NSN 5930-00-024-0870

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-024-0870

#### **Body Style:**

Hole mounted

#### Hazardous Locations/environmental Protection:

Watertight

### **Overall Length:**

3.020 inches

#### **Overall Height:**

2.857 inches

#### **Overall Width:**

1.000 inches

#### **Case Material:**

Metal

#### Actuator Style:

Round

#### **Actuator Diameter:**

0.330 inches

## Actuator Height:

1.237 inches

#### **Actuator Free Position Height:**

1.827 inches

#### Housing Height:

1.780 inches

#### Housing Length:

2.250 inches

#### Housing Width:

1.000 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.000 inches

#### Maximum Voltage Rating In Volts:

125.0 ac and 250.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### **Features Provided:**

Actuator seal

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Actuating Force:

Between 26.0 ounces and 59.0 ounces

#### **Actuator Movement:**

Between 0.160 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

# NSN 5930-00-024-0870

Sensitive Switch - Page 2 of 2



### Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 10.000 amperes resistive ac

## Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A053a0