

NSN 5930-00-026-1203 Pressure Switch - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/5930-00-026-120)3
Thread Class:	
3b single pressure connection	
Inside Diameter:	
0.500 inches single connection	
Thread Length:	
0.568 inches single pressure connection	
Overall Length:	
3.120 inches	
Body Diameter:	
1.380 inches	
Body Length:	
2.250 inches	
Overall Diameter:	
1.380 inches	
Pressure Switch Type:	
Gage	
Width Across Flats:	
0.812 inches	
Operating Tempurature Rating:	
Between -65.0 degrees fahrenheit and 160.0 degrees fahrenhei	t
Mounting Method:	
Clamp	
Thready Qty Per Inch (tpi):	
20 single pressure connection	
Contact Action Stimulus:	
Increase	
Proof Pressure:	
250 00 pounds per square inch	

250.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Sensing Element Burst Pressure:

375.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

6.00 differential point pounds per square inch gage and 10.00 differential point pounds per square inch gage and 50.00 actuation point pounds per square inch gage

NSN 5930-00-026-1203

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage Pressure Connector Type: Gasket seal, threaded internal single connection Media For Which Designed: Gas Style Designator: Cylindrical Thread Series Designator: Unf single pressure connection Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A048b0