## NSN 5930-00-026-1665

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-026-1665

| Body Style:   |
|---|
| Panel mount   |
| Hazardous Locations/environmental Protection:   |
| Fungus resistant and salt spray resistant and vibration resistant and shock resistant                                   |
| Overall Length:   |
| 1.200 inches  |
| Overall Height:   |
| 2.740 inches  |
| Overall Width:  |
| 0.960 inches  |
| Body Length:  |
| 1.195 inches  |
| Body Width:   |
| 0.800 inches  |
| Body Height:  |
| 2.740 inches  |
| Actuator Length:  |
| 0.970 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Width:   |
| 0.690 inches  |
| Actuator Color:   |
| White single actuator and white single actuator   |
| Illuminated Actuator Color:   |
| Green single actuator and amber single actuator   |
| Actuator Inscription:   |
| Console low voltage single actuator   |
| Illuminated Actuator Color Sequence:  |
| Upper left green upper right amber lower left amber lower right green   |
| Maximum Voltage Rating In Volts:  |
| 125.0 ac and 28.0 dc  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Nonpile-up Contact Arrangement:   |
| 4 pole, double throw, both positions maintained single switch unit  |
| Contact Load Current Rating At Maximum Rated Voltage:   |
| 4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac |

**Terminal Type And Quantity:** 12 turret and 5 tab, solder lug

## NSN 5930-00-026-1665

Push Switch - Page 2 of 2



| - |    |    |    |   |   |
|---|----|----|----|---|---|
| • | he | 1+ | 18 | Δ | • |
|   |    |    |    |   |   |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0