## NSN 5930-00-026-9315

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-026-9315

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Height:
2.100 inches
Overall Width:
2.250 inches
Actuator Length:
9.000 inches
Actuator Style:
Round
Actuator Width:
0.188 inches
Housing Height:
2.100 inches
Housing Length:
4.953 inches
Housing Width:
2.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.220 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.810 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
190.0 inch-ounces
Actuator Movement:
11.0 differential degrees and 17.0 pretravel degrees
Contact Load Current Rating At Maximum Rated Voltage:

4 screw

**Terminal Type And Quantity:** 

20.000 milliamperes resistive dc and 1.200 amperes resistive ac

## NSN 5930-00-026-9315

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0