NSN 5930-00-027-2313

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-027-2313
Thread Class:
2b
Body Style:
Bushing/hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
2.302 inches
Overall Width:
0.687 inches
Bushing Length:
0.610 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.990 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.142 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.327 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.180 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
End Application:
H46 aircraft
nclosure Type:
Fully enclosed
Mounting Method:
Threaded hole

32

Thready Qty Per Inch (tpi):

NSN 5930-00-027-2313 Sensitive Switch - Page 2 of 2



Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
4.0 ounces
Criticality Code Justification:
Agav
Switch Actuating Force:
30.0 ounces
Actuator Movement:
Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes inductive dc and 15.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0