

View Online at <https://aerobasegroup.com/nsn/5930-00-027-6421>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.000 inches

Overall Height:

1.125 inches

Body Diameter:

1.062 inches

Mounting Slot Width:

0.140 inches

Body Height:

0.750 inches

Distance Between Mounting Facility Centers:

1.500 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Features Provided:

Tamper proof cap

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

25.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

14.00 actuation point degrees fahrenheit and 4.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0