

View Online at <https://aerobasegroup.com/nsn/5930-00-028-0107>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Diameter:**

0.750 inches

**Bushing Length:**

0.312 inches

**Body Length:**

1.110 inches

**Actuator Diameter:**

0.500 inches

**Actuator Height:**

0.750 inches

**Actuator Color:**

Amber single actuator

**Illuminated Actuator Color:**

Amber single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.500 amperes inductive dc and 2.500 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 2.500 amperes lamp ac

**Special Features:**

Incl switch guard

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0