NSN 5930-00-028-3457

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-028-3457

Thread Class: 2b single mounting facility **Overall Length:** 4.750 inches **Overall Height:**

2.813 inches

2.906 inches **Overall Width:**

Individual Section Quantity:

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Contacts and rotor blade surfaces silver

Precious Material:

Silver

NSN 5930-00-028-3457

Rotary Switch - Page 2 of 2



Style	Design	nator:
OLYIC	Desigi	iatoi.

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0