

View Online at <https://aerobasegroup.com/nsn/5930-00-028-4190>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.406 inches

Overall Height:

3.469 inches

Overall Width:

2.000 inches

Body Height:

2.688 inches

Distance Between Mounting Facility Centers:

1.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Surface and threaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

12.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00 to 100.00 actuation point pounds per square inch and +0.00/+100.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

70.00 actuation point pounds per square inch and 30.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

240.0 ac at sea level single voltage

Pressure Connector Type:

Swivel nut, flare, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0