NSN 5930-00-028-4215

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Fungus resistant

1.000 inches



View Online at https://aerobasegroup.com/nsn/5930-00-028-4215

Center To Center Distance Between Mounting Facilities Parallel To Length:

| Body Length: |
|--|
| 1.940 inches |
| Body Width: |
| 0.687 inches |
| Body Height: |
| 1.180 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Length: |
| 1.050 inches |
| Actuator Style: |
| Roller arm |
| Actuator Free Position Height: |
| 1.422 inches |
| Actuator Roller Diameter: |
| 0.370 inches |
| Actuator Roller Width: |
| 0.150 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 1.5 ounces |
| Switch Actuating Force: |
| 6.0 ounces |
| Actuator Movement: |
| Between 0.250 pretravel inches and 0.030 overtravel inches and 0.045 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 25.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 3 screw |
| |

NSN 5930-00-028-4215

Sensitive Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0