## NSN 5930-00-028-4215

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted

Fungus resistant

1.000 inches



View Online at https://aerobasegroup.com/nsn/5930-00-028-4215

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
1.180 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
1.050 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.422 inches
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
0.150 inches
Maximum Voltage Rating In Volts:
480.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.5 ounces
Switch Actuating Force:
6.0 ounces
Actuator Movement:
Between 0.250 pretravel inches and 0.030 overtravel inches and 0.045 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
25.000 amperes resistive ac
Terminal Type And Quantity:
3 screw

## NSN 5930-00-028-4215

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0