NSN 5930-00-028-4309

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-028-4309

Thread Class:

2b single mounting facility

Overall Length:

2.395 inches

Overall Height:

1.620 inches

Overall Width:

2.000 inches

First Flat Length:

1.125 inches single actuator

Flat Height:

0.172 inches single actuator and 0.175 inches single actuator

Shaft Diameter:

0.249 inches single actuator and 0.251 inches single actuator

Shaft Length:

1.125 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.750 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Quick disconnect, male

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-028-4309

Rotary Switch - Page 2 of 2



Contact Load Current Rating

25.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0