NSN 5930-00-028-4316



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-028-4316 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.875 inches **Overall Height:** 1.062 inches **Overall Width:** 0.375 inches **Body Length:** 1.094 inches **Body Width:** 0.375 inches **Body Height:** 0.625 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:** 0.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.438 inches **Actuator Length:** 0.438 inches **Actuator Style:** Roller arm **Actuator Free Position Height:** 0.750 inches **Actuator Roller Diameter:** 0.188 inches **Actuator Roller Width:** 0.188 inches **Maximum Voltage Rating In Volts:** 250.0 ac **Inclosure Type:** Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

NSN 5930-00-028-4316

Sensitive Switch - Page 2 of 2



Contact Load Current Rating	At Maximum Rate	ed Voltage:
-----------------------------	-----------------	-------------

5.000 amperes resistive ac

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0