NSN 5930-00-028-4318

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-028-4318

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.500 inches
Body Width:
0.625 inches
Body Height:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Height:
0.063 inches
Actuator Free Position Height:
0.438 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
10.0 ounces
Actuator Movement:
Between 0.020 pretravel inches and 0.005 overtravel inches and 0.0008 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-00-028-4318

Sensitive Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A053a0