NSN 5930-00-030-3723



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-030-3723 **Body Style:** Hole mounted **Overall Length:** 1.094 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Overall Height:** 1.135 inches **Overall Width:** 0.406 inches **Body Length:** 1.094 inches **Body Width:** 0.406 inches **Body Height:** 0.625 inches **Unthreaded Mounting Hole Diameter:** 0.114 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.406 inches **Actuator Length:** 0.457 inches **Actuator Style:** Roller arm **Actuator Free Position Height:** 0.510 inches **Actuator Roller Diameter:** 0.188 inches **Actuator Roller Width:** 0.188 inches **Maximum Voltage Rating In Volts:** 250.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:**

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

14.0 ounces

NSN 5930-00-030-3723

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	·Mc	WA	mar	١+.
н	CLU	alui	IVIC	vei	пег	H.

Between 0.062 pretravel inches and 0.050 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Precious Material And Location:

Contact surfaces silver

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0