NSN 5930-00-032-9526

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-032-9526

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 4.479 inches **Overall Height:** 2.219 inches **Overall Width:** 2.063 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.000 inches single actuator **Individual Section Quantity: Operating Tempurature Range:** -65.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 13 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 13 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:**

Contact Owntoning Action.

Breaks before makes each section rear

NSN 5930-00-032-9526

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

22.5 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0