## NSN 5930-00-033-0062

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-033-0062

Dverall Length: 4.250 inches  Dverall Height: 2.500 inches  Dverall Width: 1.500 inches  Mounting Slot Width: 2.188 inches  Body Length: 1.500 inches  Body Length: 1.500 inches  Body Width: 1.500 inches  Body Width: 1.501 inches  Body Height: 1.375 inches  Distance Between Mounting Facility Centers: 2.875 inches  Capillary Tube Length: 42.0 inches  Tempurature Sensing Element Type: Capillary tube  Mounting Method: Bracket and slot  Contact Action Stimulus: Increase  Mounting Facility Pattern:  Two position in-line  Nonpile-up Contact Arrangement:
Dverall Height: 2.500 inches Dverall Width: 1.500 inches Mounting Slot Width: 0.188 inches Body Length: 1.500 inches Body Width: 1.500 inches Body Width: 1.094 inches Body Height: 1.375 inches Distance Between Mounting Facility Centers: 2.875 inches Capillary Tube Length: 42.0 inches Fempurature Sensing Element Type: Capillary tube Mounting Method: Bracket and slot Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line
2.500 inches Deverall Width: 1.500 inches Mounting Slot Width: 1.510 inches Body Length: 1.500 inches Body Width: 1.500 inches Body Width: 1.500 inches Body Width: 1.500 inches Body Height: 1.575 inches Distance Between Mounting Facility Centers: 2.875 inches Capillary Tube Length: 42.0 inches Tempurature Sensing Element Type: Capillary tube Mounting Method: Bracket and slot Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line
Dverall Width:  1.500 inches  Mounting Slot Width:  1.518 inches  Body Length:  1.500 inches  Body Width:  1.094 inches  Body Height:  1.375 inches  Distance Between Mounting Facility Centers:  2.875 inches  Capillary Tube Length:  42.0 inches  Tempurature Sensing Element Type:  Capillary tube  Mounting Method:  Bracket and slot  Contact Action Stimulus:  Increase  Mounting Facility Pattern:  Two position in-line
Mounting Slot Width:  0.188 inches  Body Length: 1.500 inches  Body Width: 1.094 inches  Body Height: 1.375 inches  Distance Between Mounting Facility Centers: 2.875 inches  Capillary Tube Length: 42.0 inches  Tempurature Sensing Element Type: Capillary tube  Mounting Method: Bracket and slot  Contact Action Stimulus: Increase  Mounting Facility Pattern: Two position in-line
Mounting Slot Width:  2.188 inches  Body Length: 1.500 inches  Body Width: 1.094 inches  Body Height: 1.375 inches  Distance Between Mounting Facility Centers: 2.875 inches  Capillary Tube Length: 42.0 inches  Tempurature Sensing Element Type: Capillary tube  Mounting Method: Bracket and slot  Contact Action Stimulus: Increase  Mounting Facility Pattern:  Two position in-line
D.188 inches  Body Length: 1.500 inches  Body Width: 1.094 inches  Body Height: 1.375 inches  Distance Between Mounting Facility Centers: 2.875 inches  Capillary Tube Length: 42.0 inches  Tempurature Sensing Element Type: Capillary tube  Mounting Method: Bracket and slot  Contact Action Stimulus: Increase  Mounting Facility Pattern: Two position in-line
Body Length:  1.500 inches  Body Width:  1.094 inches  Body Height:  1.375 inches  Distance Between Mounting Facility Centers:  2.875 inches  Capillary Tube Length:  42.0 inches  Tempurature Sensing Element Type:  Capillary tube  Mounting Method:  Bracket and slot  Contact Action Stimulus:  Increase  Mounting Facility Pattern:  Two position in-line
1.500 inches Body Width: 1.094 inches Body Height: 1.375 inches Distance Between Mounting Facility Centers: 2.875 inches Capillary Tube Length: 42.0 inches Tempurature Sensing Element Type: Capillary tube Mounting Method: Bracket and slot Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line
Body Width:  1.094 inches  Body Height:  1.375 inches  Distance Between Mounting Facility Centers:  2.875 inches  Capillary Tube Length:  42.0 inches  Tempurature Sensing Element Type:  Capillary tube  Mounting Method:  Bracket and slot  Contact Action Stimulus:  ncrease  Mounting Facility Pattern:  Two position in-line
1.094 inches Body Height: 1.375 inches Distance Between Mounting Facility Centers: 2.875 inches Capillary Tube Length: 42.0 inches Tempurature Sensing Element Type: Capillary tube Mounting Method: Bracket and slot Contact Action Stimulus: ncrease Mounting Facility Pattern: Two position in-line
Body Height:  1.375 inches  Distance Between Mounting Facility Centers:  2.875 inches  Capillary Tube Length:  42.0 inches  Tempurature Sensing Element Type:  Capillary tube  Mounting Method:  Bracket and slot  Contact Action Stimulus:  Increase  Mounting Facility Pattern:  Two position in-line
Distance Between Mounting Facility Centers:  2.875 inches  Capillary Tube Length:  42.0 inches  Tempurature Sensing Element Type:  Capillary tube  Mounting Method:  Bracket and slot  Contact Action Stimulus:  Increase  Mounting Facility Pattern:  Two position in-line
Distance Between Mounting Facility Centers:  2.875 inches  Capillary Tube Length:  42.0 inches  Tempurature Sensing Element Type:  Capillary tube  Mounting Method:  Bracket and slot  Contact Action Stimulus:  ncrease  Mounting Facility Pattern:  Two position in-line
2.875 inches  Capillary Tube Length: 42.0 inches  Tempurature Sensing Element Type: Capillary tube  Mounting Method: Bracket and slot  Contact Action Stimulus: Increase  Mounting Facility Pattern: Two position in-line
Capillary Tube Length: 42.0 inches Fempurature Sensing Element Type: Capillary tube Mounting Method: Bracket and slot Contact Action Stimulus: ncrease Mounting Facility Pattern: Two position in-line
42.0 inches Fempurature Sensing Element Type: Capillary tube Mounting Method: Bracket and slot Contact Action Stimulus: ncrease Mounting Facility Pattern: Two position in-line
Tempurature Sensing Element Type: Capillary tube  Mounting Method: Bracket and slot  Contact Action Stimulus: ncrease  Mounting Facility Pattern: Two position in-line
Capillary tube  Mounting Method: Bracket and slot  Contact Action Stimulus: Increase  Mounting Facility Pattern: Two position in-line
Mounting Method: Bracket and slot Contact Action Stimulus: ncrease Mounting Facility Pattern: Two position in-line
Bracket and slot  Contact Action Stimulus: ncrease  Mounting Facility Pattern: Two position in-line
Contact Action Stimulus: Increase  Mounting Facility Pattern: Two position in-line
ncrease  Mounting Facility Pattern:  Two position in-line
Mounting Facility Pattern: Two position in-line
Two position in-line
·
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
20.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+4.00/+45.00 actuation point degrees fahrenheit and +4.00 to 45.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point knob and external actuation point knob

Frequency In Hertz:

60.0 single voltage

## NSN 5930-00-033-0062

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0