NSN 5930-00-033-3298

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-033-3298

Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
3.620 inches
Outside Diameter:
0.250 inches single connection
Body Length:
2.125 inches
Overall Diameter:
2.000 inches
Pressure Switch Type:
Gage
Width Across Flats:
0.880 inches
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Clamp
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Thread Size:
0.250 inches single pressure connection
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
10.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
18.00 actuation point pounds per square inch and 22.00 actuation point pounds per square inch
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Pressure Connector Type:
Flared, threaded external single connection
Media For Which Designed:
Liquid
Style Designator:
Cylindrical

NSN 5930-00-033-3298

Pressure Switch - Page 2 of 2



Thread Series Designato	TI	nread	Series	Design	ator
-------------------------	----	-------	--------	--------	------

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0