

View Online at <https://aerobasegroup.com/nsn/5930-00-034-0572>

**Body Style:**

Hole mounted

**Actuator Style:**

Round

**Actuator Diameter:**

0.244 inches

**Actuator Height:**

0.759 inches

**Actuator Free Position Height:**

0.759 inches

**Housing Height:**

1.125 inches

**Housing Length:**

3.937 inches

**Housing Width:**

2.250 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.437 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.875 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**End Application:**

Taircraft stratofortress b-52, stratolifter c135, galaxy c-5, awacs e-3a, engine aircraft tf33-pw-10 (c135e, ec-135h/k/p), engine aircraft tf33-p-3/5/9(c/ec-135, b-52h)engine aircraft tf-33-p-7(c-141a/b) , joint stars target radar system

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

23.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

50.0 ounces

**Actuator Movement:**

59.0 pretravel degrees and 138.0 overtravel degrees and 5.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0