

View Online at <https://aerobasegroup.com/nsn/5930-00-034-0572>

Body Style:

Hole mounted

Actuator Style:

Round

Actuator Diameter:

0.244 inches

Actuator Height:

0.759 inches

Actuator Free Position Height:

0.759 inches

Housing Height:

1.125 inches

Housing Length:

3.937 inches

Housing Width:

2.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.437 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.875 inches

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

End Application:

Taircraft stratofortress b-52, stratolifter c135, galaxy c-5, awacs e-3a, engine aircraft tf33-pw-10 (c135e, ec-135h/k/p), engine aircraft tf33-p-3/5/9(c/ec-135, b-52h)engine aircraft tf-33-p-7(c-141a/b) , joint stars target radar system

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

23.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

50.0 ounces

Actuator Movement:

59.0 pretravel degrees and 138.0 overtravel degrees and 5.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0