NSN 5930-00-034-5112

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-034-5112

Thread Class: 2b single mounting facility Overall Length: 4.875 inches Overall Height: 2.781 inches Overall Width: 2.781 inches Individual Section Quantity: 6 Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type: Tab w/screw
Overall Length: 4.875 inches Overall Height: 2.781 inches Overall Width: 2.781 inches Individual Section Quantity: 6 Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting: 4 single actuator Terminal Type:
4.875 inches Overall Height: 2.781 inches Overall Width: 2.781 inches Individual Section Quantity: 6 Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Overall Height: 2.781 inches Overall Width: 2.781 inches Individual Section Quantity: 6 Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
2.781 inches Overall Width: 2.781 inches Individual Section Quantity: 6 Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Overall Width: 2.781 inches Individual Section Quantity: 6 Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Individual Section Quantity: 6 Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Individual Section Quantity: 6 Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Knob Manufacturer Code: 82121 Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Knob Specificationial Markings: Arrow sign Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Nonpile-up nonsymmetrical Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Mounting Facility Circle Radius: 1.610 inches single mounting facility Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Mounting Method: Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Bracket single mounting facility and threaded hole single mounting facility Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Features Provided: Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Thready Qty Per Inch (tpi): 20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
20 single mounting facility Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Thread Size: 0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
0.250 inches single mounting facility Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Contact Voltage Rating In Volts: 500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
500.0 ac at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
Switch Actuator Indexing Position Quantity: 4 single actuator Terminal Type:
4 single actuator Terminal Type:
Terminal Type:
Tab w/screw
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
30.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:

Unc single mounting facility

NSN 5930-00-034-5112

Rotary Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0