## NSN 5930-00-034-5141

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-034-5141

**Overall Length:** 

0.781 inches

**Overall Height:** 

0.844 inches

## **Overall Width:**

1.060 inches

Body Length:

0.562 inches

#### **Unthreaded Mounting Hole Diameter:**

0.120 inches

### Longest Horizontal Distance Between Mounting Centers:

0.750 inches

Longest Vertical Distance Between Mounting Centers:

0.565 inches

#### **Operating Tempurature Rating:**

Between 0.0 degrees celsius and 55.0 degrees celsius

**Mounting Method:** 

Unthreaded hole

**Contact Action Stimulus:** 

Increase

Mounting Facility Pattern:

Two position diagonal

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

**Terminal Type:** 

Tab, solder lug

**Contact Load Current Rating:** 

5.0 amperes resistive load single voltage

#### **Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

#### **Contact Stimulus Rating:**

1760.00 actuation point feet per minute and 1580.00 deactuation point feet per minute

## **Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

## Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

## Precious Material And Location:

Contacts silver

## **Precious Material:**

Silver

# NSN 5930-00-034-5141

Flow Switch - Page 2 of 2

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

