

View Online at <https://aerobasegroup.com/nsn/5930-00-035-4739>

**Thread Class:**

3a single pressure connection

**Body Length:**

1.690 inches

**Overall Diameter:**

1.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

0.663 inches

**Longest Vertical Distance Between Mounting Centers:**

0.663 inches

**Pressure Switch Type:**

Absolute

**Operating Temperature Rating:**

Between -55.0 degrees fahrenheit and 72.0 degrees fahrenheit

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

50.00 pounds per square inch

**Thread Size:**

0.4375 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire loop

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

12.00 actuation point pounds per square inch absolute and 14.00 deactuation point pounds per square inch absolute and 2.00 differential point pounds per square inch absolute

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0