

View Online at <https://aerobasegroup.com/nsn/5930-00-035-4739>

Thread Class:

3a single pressure connection

Body Length:

1.690 inches

Overall Diameter:

1.375 inches

Longest Horizontal Distance Between Mounting Centers:

0.663 inches

Longest Vertical Distance Between Mounting Centers:

0.663 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -55.0 degrees fahrenheit and 72.0 degrees fahrenheit

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

50.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire loop

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

12.00 actuation point pounds per square inch absolute and 14.00 deactuation point pounds per square inch absolute and 2.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0