## NSN 5930-00-036-6163

Rotary Switch - Page 1 of 2

0.375 inches single mounting facility

**Thread Class:** 

Thread Length:

**Overall Length:** 

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-036-6163

3.750 inches **Overall Height:** 2.375 inches **Overall Width:** 2.000 inches **Shaft Diameter:** 0.250 inches 1st actuator **Shaft Length:** 1.000 inches 2nd actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 3rd section rear **Throw Quantity:** 8 2nd section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Rotor Through Connection Quantity:** 1 2nd section **Switch Actuator Indexing Position Quantity:** 8 1st actuator **Shaft Type:** Round, hollowed 1st actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 20.0 degrees all actuators **Switch Actuator Stop Device Type:** Fixed stop all actuators

## NSN 5930-00-036-6163

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

350.0 milliamperes resistive load ac at sea level

**Precious Material And Location:** 

Contacts and rotor surfaces silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0