NSN 5930-00-037-9479

Thermostatic Switch - Page 1 of 2

Pivoted frame mtg



View Online at https://aerobasegroup.com/nsn/5930-00-037-9479

Overall Height:
2.125 inches
Body Diameter:
5.750 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Distance Between Mounting Facility Centers:
2.000 inches
Capillary Tube Length:
144.0 inches
Bulb Length:
3.000 inches
Bulb Diameter:
0.688 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
220.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
5.0 amperes resistive load third voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+100.00 to 200.00 actuation point degrees fahrenheit and +100.00 to 200.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point knob and external actuation point knob
Contact Voltage Rating In Volts:
230.0 dc at sea level third voltage
Special Features:

NSN 5930-00-037-9479 Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Disc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0