

View Online at <https://aerobasegroup.com/nsn/5930-00-038-0698>

**Thread Class:**

2b 1st mounting facility

**Overall Length:**

7.000 inches

**Overall Height:**

2.828 inches

**Overall Width:**

3.375 inches

**First Flat Length:**

0.750 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.625 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.250 inches 2nd mounting facility

**Individual Section Quantity:**

13

**Knob Manufacturer Code:**

82121

**Knob Specification Markings:**

Arrow symbol

**Longest Horizontal Distance Between Mounting Centers:**

3.750 inches 2nd mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.250 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

20 1st mounting facility

**Thread Size:**

0.250 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load lowest ac voltage rating at sea level

**Special Features:**

Ten amp switch mtd on 30 amp frame

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0