

View Online at <https://aerobasegroup.com/nsn/5930-00-038-0698>

Thread Class:

2b 1st mounting facility

Overall Length:

7.000 inches

Overall Height:

2.828 inches

Overall Width:

3.375 inches

First Flat Length:

0.750 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.625 inches single actuator

Unthreaded Mounting Hole Diameter:

0.250 inches 2nd mounting facility

Individual Section Quantity:

13

Knob Manufacturer Code:

82121

Knob Specification Markings:

Arrow symbol

Longest Horizontal Distance Between Mounting Centers:

3.750 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.250 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 1st mounting facility

Thread Size:

0.250 inches 1st mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load lowest ac voltage rating at sea level

Special Features:

Ten amp switch mtd on 30 amp frame

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0