

View Online at <https://aerobasegroup.com/nsn/5930-00-038-6148>

Hazardous Locations/environmental Protection:

Raintight

Overall Length:

2.156 inches

Overall Height:

4.406 inches

Overall Width:

2.251 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Capillary Tube Length:

120.000 inches

Bulb Length:

2.500 inches

Bulb Diameter:

0.290 inches

Longest Horizontal Distance Between Mounting Centers:

1.563 inches

Longest Vertical Distance Between Mounting Centers:

2.938 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

190.0 degrees fahrenheit

Mounting Method:

Surface and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

22.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00 to 150.00 actuation point degrees fahrenheit and +0.00/+150.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

277.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0