

View Online at <https://aerobasegroup.com/nsn/5930-00-038-6148>

**Hazardous Locations/environmental Protection:**

Raintight

**Overall Length:**

2.156 inches

**Overall Height:**

4.406 inches

**Overall Width:**

2.251 inches

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Capillary Tube Length:**

120.000 inches

**Bulb Length:**

2.500 inches

**Bulb Diameter:**

0.290 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.563 inches

**Longest Vertical Distance Between Mounting Centers:**

2.938 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Operating Temperature Rating:**

190.0 degrees fahrenheit

**Mounting Method:**

Surface and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

22.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.00 to 150.00 actuation point degrees fahrenheit and +0.00/+150.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

277.0 ac at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0