

View Online at <https://aerobasegroup.com/nsn/5930-00-039-7325>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.188 inches

Overall Height:

4.500 inches

Overall Width:

1.562 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

45.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.75/+30.75 actuation point pounds per square inch and +0.00 to 30.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Stimulus Rating:

0.75 differential point pounds per square inch

Contact Voltage Rating In Volts:

250.0 ac at sea level second voltage

Pressure Connector Type:

Swivel nut, flareless, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0