

View Online at <https://aerobasegroup.com/nsn/5930-00-041-1711>

Thread Class:

2a single mounting facility

Thread Length:

0.468 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.063 inches

First Flat Length:

0.313 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

2.219 inches single actuator

Overall Diameter:

2.000 inches

Individual Section Quantity:

3

Nonturn Device Type:

Slotted bushing at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

2 each section front

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, nonparallel flattened single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0