

View Online at <https://aerobasegroup.com/nsn/5930-00-041-1735>

Thread Class:

3a single pressure connection

Thread Length:

0.250 inches single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

2.000 inches

Outside Diameter:

0.375 inches single connection

Body Length:

1.063 inches

Overall Diameter:

1.000 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -55.0 degrees fahrenheit and 125.0 degrees fahrenheit

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

24 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

30.00 pounds per square inch

Thread Size:

0.375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire hook

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

9.50 actuation point pounds per square inch absolute and 11.50 deactuation point pounds per square inch absolute and 2.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A048b0