

View Online at <https://aerobasegroup.com/nsn/5930-00-043-2714>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

1.469 inches

Body Width:

0.672 inches

Body Height:

1.094 inches

Unthreaded Mounting Hole Diameter:

0.141 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Height:

0.219 inches

Actuator Free Position Height:

0.934 inches

Maximum Voltage Rating In Volts:

110.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

64.0 ounces

Actuator Movement:

Between 0.022 pretravel inches and 0.010 overtravel inches and 0.009 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 25.000 amperes resistive ac

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0