

View Online at <https://aerobasegroup.com/nsn/5930-00-043-3861>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.188 inches single mounting facility

**Overall Length:**

2.870 inches

**Overall Height:**

1.380 inches

**Overall Width:**

1.020 inches

**First Flat Length:**

0.310 inches single actuator

**Flat Height:**

0.093 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.442 inches single actuator

**Nonturn Device Radius:**

0.250 inches at 6: 00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Pin at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Cam actuated

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Cam Actuated Switch Contact Arrangement:**

3 pole, double throw, one position momentary each switch each section in-line

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section in-line

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0