

View Online at <https://aerobasegroup.com/nsn/5930-00-044-4108>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

Between 1.305 inches and 1.335 inches

Overall Height:

2.990 inches

Overall Width:

Between 0.875 inches and 0.905 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

Between 1.305 inches and 1.335 inches

Body Width:

Between 0.875 inches and 0.905 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

Between 1.335 inches and 1.365 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0