

View Online at <https://aerobasegroup.com/nsn/5930-00-044-4108>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

Between 1.305 inches and 1.335 inches

**Overall Height:**

2.990 inches

**Overall Width:**

Between 0.875 inches and 0.905 inches

**Bushing Length:**

Between 0.455 inches and 0.485 inches

**Body Length:**

Between 1.305 inches and 1.335 inches

**Body Width:**

Between 0.875 inches and 0.905 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Height:**

1.140 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

Between 1.335 inches and 1.365 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0