

View Online at <https://aerobasegroup.com/nsn/5930-00-044-4144>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Overall Length:**

2.035 inches

**Overall Height:**

2.780 inches

**Overall Width:**

0.520 inches

**Body Length:**

1.660 inches

**Body Width:**

0.520 inches

**Body Height:**

2.100 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.812 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.375 inches

**Actuator Free Position Height:**

0.375 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 250.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Actuator Movement:**

0.188 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 100.000 milliamperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 tab w/screw

**Specification Data:**

96906-ms16106 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0

**Mil-std (military Standard):**

Mil-s-8805 spec.