

View Online at <https://aerobasegroup.com/nsn/5930-00-045-0522>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.400 inches

Actuator Length:

0.875 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.662 inches

Actuator Roller Diameter:

0.188 inches

Actuator Roller Width:

0.188 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.156 pretravel inches and 0.062 overtravel inches and 0.045 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0