# NSN 5930-00-049-7160

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-049-7160

## Thread Class:

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.062 inches

## Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.500 inches single actuator

### **Overall Diameter:**

1.156 inches

### **Nonturn Device Radius:**

0.531 inches at 2: 30 o'clock

## Individual Section Quantity:

2

### Nonturn Device Type:

Tab at 2: 30 o'clock

## **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

### Switch Contact Basic Design:

Nonpile-up symmetrical

### Pole Quantity:

3 each section rear

### **Throw Quantity:**

3 each section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

3 single actuator

## Shaft Type:

Round single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-049-7160

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

500.0 milliamperes resistive load ac at sea level

#### **Precious Material And Location:**

Contact surfaces silver

**Precious Material:** 

Silver

## Style Designator:

Circular wafer, bushing mount

### Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0