NSN 5930-00-049-7849

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-049-7849

Thread Class: 2b single mounting facility **Overall Length:** 7.438 inches **Overall Height:** 5.000 inches **Overall Width:** 3.875 inches First Flat Length: 0.375 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.938 inches single actuator **Individual Section Quantity:** 2 **Longest Horizontal Distance Between Mounting Centers:** 4.500 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical and nonpile-up nonsymmetrical **Pole Quantity:** 1 1st section front **Throw Quantity:** 5 1st section front **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:**

Tab, solder lug

NSN 5930-00-049-7849

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes 2nd section rear **Switch Actuator Positioning Increment:** 36.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

Style Designator:

Circular wafer, panel mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0