NSN 5930-00-049-7849

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-049-7849

Thread Class:

2b single mounting facility

Overall Length:

7.438 inches

Overall Height:

5.000 inches

Overall Width:

3.875 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.938 inches single actuator

Individual Section Quantity:

```
2
```

Longest Horizontal Distance Between Mounting Centers:

4.500 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 1st section front

Throw Quantity:

5 1st section front

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

NSN 5930-00-049-7849

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes 2nd section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level Style Designator: Circular wafer, panel mount **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization:

No

Fiig:

A052b0