

View Online at <https://aerobasegroup.com/nsn/5930-00-050-1194>

Body Style:

Hole mounted

Overall Length:

0.790 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Width:

0.260 inches

Body Length:

0.790 inches

Body Width:

0.260 inches

Body Height:

0.440 inches

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.450 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0