

View Online at <https://aerobasegroup.com/nsn/5930-00-050-1194>

**Body Style:**

Hole mounted

**Overall Length:**

0.790 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Overall Width:**

0.260 inches

**Body Length:**

0.790 inches

**Body Width:**

0.260 inches

**Body Height:**

0.440 inches

**Unthreaded Mounting Hole Diameter:**

0.087 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.100 inches

**Actuator Width:**

0.125 inches

**Actuator Free Position Height:**

0.450 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0