NSN 5930-00-050-2522

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-050-2522

Thread Class:

2a single mounting facility

Thread Length:

0.313 inches single mounting facility

Overall Length:

2.755 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.000 inches single actuator

Overall Diameter:

1.750 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-050-2522

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0