

View Online at <https://aerobasegroup.com/nsn/5930-00-050-5264>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.620 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.812 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.835 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

Whidbey island class lsd, forrestral class cv, supply class aoe, nimitz class cvn, cimmaron class ao, wichita class aor, wasp class lhd, emory s.Land class as, yellowstone class ad-41, shipboard material handeling equipmen (mhe)

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

0.010 inch-ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

0.720 inch-ounces

Actuator Movement:

Between 1.200 pretravel inches and 1.140 overtravel inches and 0.330 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0