

View Online at <https://aerobasegroup.com/nsn/5930-00-050-9525>

Thread Class:

3b all threaded hole

Overall Length:

4.922 inches

Body Diameter:

0.625 inches

Body Length:

3.594 inches

Overall Diameter:

1.750 inches

Distance Between Mounting Facility Centers:

1.082 inches

Tempurature Sensing Element Type:

Immersion well

Operating Tempurature Rating:

Between -100.0 degrees fahrenheit and 600.0 degrees fahrenheit

Mounting Method:

Flange and threaded hole

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-100.00 to 400.00 actuation point degrees fahrenheit and -100.00/+400.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

75.00 actuation point degrees fahrenheit and 70.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0